

SETON

RE-SEAL TUBES Polyallomer Thin Wall *Ultra*

707-782-0900
707-782-0902 fax
sales@setonscientific.com
P.O. Box 750003
Petaluma, CA 94975 USA

RE-SEAL POLYALLOMER TUBES FOR HEAT SEALING & RE-SEAL PLUGS

Rev.3

Tube Size	Seton PN Box of 50	Tube Volume ml	Max Speed KRPM	Crown PN Seton (Beckman)	For Beckman Rotor	For Thermo-Rotor	Like Beckman Tube PN	Like Thermo-Sorvall Tube PN	Thermo Sorvall Crown PN
1/2x1-1/2" (13x45mm)	9021(2)	3.9	100	(342883)	TLN100	---	358980	---	---
1/2x2" (13x51mm)	9022(2)	5.1		(342883)	NVT100,NVT90 VTI90,VTI65.2	70V6	342412	---	79291
1/2x2" (13x51mm)	9028(1)	5.1	100	4257(3)	---	S100-AT6	---	45248	45321
1/2x2" (13x51mm)	3022(2)	5.1		(342883)	NVT100,NVT90 VTI90,VTI65.2	70V6	344075	---	79291
5/8x2" (16x53mm)	9042	8.3	80	4491(3)	---	S80-AT3	---	45597	45599
5/8x3" (16x76mm)	9041(2)	10		(342695,349289)	90Ti,70,1Ti NVT65,VTI65.1	---	342413	---	---
5/8x3" (16x76mm)	9041R(1)	13.5	75 65	4068(3)(6) 4069(3)	90Ti,80Ti,75Ti 70,1Ti,1y65	---	---	---	---
5/8x3" (16x76mm)	3041(2)	13.5	65	4068(3) 4069(3)	90Ti,70,1Ti NVT65,VTI65.1	---	344322	---	---
5/8x3" (16x78mm)	9043	13.5	58	4491(3)	---	S58A	---	45809	45599
1x3" (25x76mm)	9054	30	55	4146(3)	---	S55-A	---	75000514	75000521
1x3-1/2" (25x89mm)	9052(2)	39	70	(342699,342417)	70Ti,60Ti,55.2Ti 50.2Ti,VTI50	---	342414	---	---
1x3-1/2" (25x89mm)	9053(1)	39	60	4065(3)	70Ti,60Ti,55.2Ti 50.2Ti	---	---	---	---
1x3-1/2" (25x89mm)	3052(2)	39	70	(342699,342417)	70Ti,VTI50	---	344326	---	---
1-1/2x4" (38x1022mm)	9060(5)	94	45	4492	45Ti	---	345776	---	---

©2000-2016 Seton Scientific

NOTES:

- (1) Stem is .260" long for use with Re-Seal plugs.
- (2) Stem is .310" long for use with Beckman heat sealer.
- (3) Use Seton Re-Seal Plug PN 4075.
- (4) Tube is Sorvall hole size which is slightly smaller than the Beckman standard.
- (5) Box of 25 tubes.
- (6) The difference between 4068 and 4069 corresponds to the difference in the rotor counterbore diameters.